

FIXOPRIME BT

Back Tile/Stone Primer for Demanding Tiling Application on Challenging Substrates

- ◆ **FIXOPRIME BT** is a high performance, single-component ready to use acrylic ester based back tile primer recommended for highly vitrified tiles.
- ◆ It is an excellent adhesion promoter for low porosity non absorbing latest vitrified tiles and gypsum or ply board.

RECOMMENDED APPLICATIONS

- ◆ Highly Vitrified Tiles
- ◆ Artificial Marble
- ◆ Wooden Tiles
- ◆ Non-Porous Tiles & Stones
- ◆ Flexible Tiles

KEY FEATURES & BENEFITS



Excellent penetration on the tile/stone for bonding



Easy application by brush/roller



Excellent Dual Bonding & Durability



Fast drying after the single coat application



Acts as a waterproofing membrane

TECHNICAL SPECIFICATIONS¹ (Complies to ASTM C 627 for residential & commercial applications)

Appearance	: Off White Creamy Paste
Specific Gravity	: 1.45 ± 0.05 Kg/l
Solids	: 55 ± 2 %
Tensile Adhesion Strength	: ≥ 2 N/mm ² on concrete, screed, gypsum & plywood
Touch Dry Time	: 25 ± 5 minutes
Shear Adhesion	: ≥ 2 N/mm ² for concrete, screed, plaster, gypsum or ply board
Acid, Alkali & Chemical Resistance	: Excellent

COVERAGE

50 - 60 ft² / coat / 1Kg
(Depending on the surface)

SHELF LIFE

12 months from the date of manufacturing.



Packaging : Available in
1, 5 & 20 Kg bucket

¹ The values obtained are from laboratory testing conditions at $27 \pm 2^\circ\text{C}$. On site tests may show slight variation due to site conditions and/or methods of testing/application. Follow company TDS to obtain best results.